

Pelco Sarix HD Demo Kit Offer



One per customer only

ADI Product Code: 808-0303



by **Schneider** Electric

**STANDARD
PACKAGE PRICE:**

£2,451

PACKAGE OFFER PRICE:

£420

1x DS4U Four channel software recording

- Four-channel, software-only recording solution.
- Use DS4U to manage and record four Pelco IP cameras
- Upgradeable to DS NVs to record up to 64 channels of Pelco or third-party IP camera systems
- DS4U supports Standard-Definition (SD) and High-Definition (HD) camera
- Records H.264, MJPEG, and additional compression streams
- Configure the recording rate on a per-camera basis
- Motion or continuous recording

1 x IXE20DN Sarix 2.1 Megapixel day/night camera

- Up to 2.1 Megapixel Resolution (1920 x 1080)
- Up to 30 Images per Second (ips) at 1920 x 1080
- Auto Back Focus
- H.264 and MJPEG Compression Capability
- Video Setup Jack
- Sensitivity Down to 0.05 lux
- Power over Ethernet (IEEE 802.3af) or 24 VAC
- Up to 2 Simultaneous Video Streams
- Web Viewing, up to 16 Cameras Simultaneously
- Local Storage (Mini SD) for Alarm Capture

Available from ADI Global Distribution



T: 0161 767 2970

E: info.uk@adiglobal.com

W: www.adiglobal.com/uk

To place your order please contact your local Branch, Area Account Manager or call our Central Sales Team on 0161 767 2990.

1 X IDE20DN8-1 Sarix 2.1 Megapixel day/night static dome

- Up to 2.1 Megapixel Resolution (1920 x 1080)
- Up to 30 Images per Second (ips) at 1080p
- Optional CS Mount Lenses
- Auto Back Focus for High Precision Focusing
- H.264 and MJPEG Compression
- Day/Night Capability
- Sensitivity Down to 0.03 lux
- Power over Ethernet (IEEE 802.3af) or 24 VAC
- Video Setup Jack and Focus Button Accessible with Dome Closed
- Up to 2 Simultaneous Video Streams
- Web Viewing, up to 16 Cameras Simultaneously
- Local Storage (Micro SD) for Alarm Capture
- 2.8-8mm MegaPixel lens

1 x 13M2.8-8 MegaPixel lens

- | 2.8-8mm MegaPixel lenses

1 x IM10C10-1 1.3 Megapixel Static Mini-Dome

- | Up to 1.3 Megapixel Resolution (1280 x 1024)
- | Up to 30 Images per Second (ips) at 1280 x 720
- | Compact Size with 3-inch Bubble
- | Auto Focus Varifocal 2.8~10 mm Megapixel Lens
- | Easy Installation
- | H.264 and MJPEG Compression
- | Sensitivity Down to 0.12 lux
- | Line-in Audio and Built-in Microphone
- | Power over Ethernet (PoE), IEEE 802.3af
- | Video Setup Jack Accessible with Dome Installed
- | Up to 2 Simultaneous Video Streams
- | Web Viewing, up to 16

Written terms and conditions available on request.