



VIMPEX FIRE CRYER® RANGE

These innovative voice sounders from Vimpex can broadcast up to four messages on a conventional two wire sounder circuit. Easily interfaced to both new and existing systems, the five Fire-Cryer® models in the range meet every requirement from residential and light commercial to heavy industrial applications. Any four message combinations can be specified and selected, either automatically or manually, at the fire alarm control panel. Foreign language and multi-lingual units are also available. Versatile software also allows for simple interface with loop sounder modules. The Fire-Cryer® range provides simple, cost-effective, fully synchronised voice annunciation for all forms of evacuation and information broadcast.

## VOICE SOUNDERS

Code

### VIMPEX (1 Year Warranty)

#### FIRE-CRYER® VOICE ENHANCED SOUNDERS - 95-100 DBA @ 24V dc

700-0306 **F/A/1** Single message synchronised Fire-Cryer®700-0307 **F/A/4** Multi-message synchronised Fire-Cryer®700-0308 **BM81290** Deep base for above sounders (required to achieve IP65 rating)620-0440 **8502100** Flush mounting ring700-0310 **8502700** Mains pack. 230V AC input, 24V dc output700-0311 **8503000** Xenon strobe/sounder combination bracket for Banshee/Bedlam, Fire-Cryer®, Bell or Strobe618-0422 **EASYAV/B** Smart Strobe Conversion, used to upgrade a standard wall-mounted Fire-Cryer® to a sounder/strobe unit

#### MINI FIRE-CRYER® VOICE ENHANCED SOUNDERS - 86-90 DBA @ 24V dc

700-0312 **F/C/1** Single message synchronised Mini Fire-Cryer®700-0313 **F/C/4** Multi-message Synchronised Mini Fire-Cryer®700-0314 **8502800** Cable spacing ring for above sounders

#### MIDI FIRE-CRYER® VOICE ENHANCED SOUNDERS - 104-110 DBA @ 24V dc

700-0315 **F/B/1** Single message synchronised Midi Fire-Cryer®700-0316 **F/B/4** Multi-message synchronised Midi Fire-Cryer®700-0317 **BBX-4** Back Box, recommended for surface mount installations

#### MAXI FIRE-CRYER® VOICE ENHANCED SOUNDERS - 112-116 DBA @ 24V dc

700-0318 **F/D/1** Single message synchronised Maxi Fire-Cryer®700-0319 **F/D/4** Multi-message synchronised Maxi Fire-Cryer®

#### ANI-MATE® ANIMAL FRIENDLY VOICE ENHANCED SOUNDER

700-0320 **F/E/4** Multi-message low frequency synchronised Fire-Cryer®

#### FIRE-CRYER® SWITCHING INTERFACES

700-0321 **F/S/4** Multi-message switching PCB700-0322 **F/S/VMC** Voice message controller (VMC) complete with F/S/4 PCB

#### FIRE-CRYER® DEMONSTRATION UNIT

700-0323 **F/Z/DEMO** Four message hand-held demonstration unit (requires two 9V batteries)

#### FIRE-CRYER® INTELLIGENT STROBE MODULES

700-0324 **F/M/STROBE/F** Alarm/Alert Twin Strobe Module700-0325 **F/M/STROBE/4** Alarm Strobe Module plus F/A/4, multi-message Fire-Cryer®700-0326 **F/M/STROBE/F1** Alarm Strobe Module only (includes bracket and strobe)

The Fire Cryer® Range of Voice Sounders has become firmly established as the market leader. Vimpex are able to advise on all technical matters including the interfacing of the Fire-Cryer® range with all types of conventional and addressable fire alarm control panels.